



MOHM CHEMICAL SDN. BHD. (Co.No.276851-U)
MCX MARKETING SDN. BHD. (Co.No.363532-T)

H.Q. : No.32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor, Malaysia.
 Tel : (60 7) 333 1222 Fax : (60 7) 332 0545 / 333 7919
 Branch : No.43, Jalan Tambur 33/19, Sek. 33, Shah Alam Technology Park,
 47100 Shah Alam, Selangor, Malaysia.
 Tel: (60 3) 5124 0876 / 5124 0878 Fax: (60 3) 5124 0877
 Email: info@mochem.com Website: www.mochem.com / www.xtraseal.com



MATERIAL SAFETY DATA SHEET

xtraseal® LOW VOC MC-800 ACRYLIC SEALANT



1. Product & Company Identification

1.1 Product Detail	
Product name:	Low VOC MC-800 Acrylic Sealant
Physical form:	Paste
Odour:	Mild Acrylic Odour
CAS No.:	Mixture
Flammability:	Material may not burn in wet state
1.2 Company Details:	
Manufacturer:	Mohm Chemical Sdn Bhd
Address:	No. 32 (Lot 1617), Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor, Malaysia.
Tel:	+ 60-7-3331222
Fax:	+ 60-7-3320545/ + 60-7-3337919

2. Composition/ Hazardous Components

<u>Chemical Name</u>	<u>CAS No.</u>	<u>Approx WT%</u>
Plasticizer	117-81-7	<5%
Ethylene glycol	107-21-1	1-10%
Mineral Spirits	64742-48-9	1-5%

3. Hazards Identification

Ingestion:	None known
Skin contact:	Uncured product contact may irritate the skin.
Eye contact:	Uncured product contact irritates eyes.
Inhalation:	May cause mild respiratory irritation.

4. First-aid Measures

Take off all contaminated clothing immediately.
 In case of ingestion: Seek medical advice immediately.
 In case of skin contact: Wipe with paper towel and immediately clean with water and soap.
 In case of eyes contact: Immediately flush with water, seek medical advice if necessary.



MOHM CHEMICAL SDN. BHD. (Co.No.276851-U)
MCX MARKETING SDN. BHD. (Co.No.363532-T)

H.Q. : No.32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor. Malaysia.
 Tel : (60 7) 333 1222 Fax : (60 7) 332 0545 / 333 7919
 Branch : No.43, Jalan Tambur 33/19, Sek. 33, Shah Alam Technology Park,
 47100 Shah Alam, Selangor. Malaysia.
 Tel: (60 3) 5124 0876 / 5124 0878 Fax: (60 3) 5124 0877
 Email: info@mochem.com Website: www.mochem.com / www.xtraseal.com



MATERIAL SAFETY DATA SHEET

xtraseal® LOW VOC MC-800 ACRYLIC SEALANT



5. Fire Fighting Measures

Suitable extinguishing media: Water, foam, CO2, dry power and all standard fire-fighting media.
 Unsuitable extinguishing media: Unknown
 Hazardous decomposition: Not specified.

6. Accidental release measures

Methods for cleaning up: Take up mechanically.

7. Handling and Storage

Handling: Ensure good ventilation during processing. Wear safety shoes.
 Protection against fire/ explosion: General rules of fire prevention should be observed.
 Storage: Keep container tightly closed and dry.
 Cautions: Extreme heavy in drum form if product packed in 200L drum.

8. Exposure control/ Personal protection

Ingredients with limited values to be controlled: Not indicated.
 Local exhaust: Recommended
 General ventilation: Recommended
 Hand protection: Suitable protective gloves.
 Eye protection: Safety/protective glasses.

9. Physical and Chemical Properties

Form: Paste
 Specific gravity: 1.60 +/- 0.05
 Colour: Applied Milky White but turn clear after dry
 Viscosity: Not indicated.
 Odour: Mild Acrylic Odour
 Volatile % (25°C): < 45%
 Solubility in water: Yes
 Boiling point: 100°C
 Flash point: Non known
 Ignition temperature: Non known

Note: the above information is not intended for use in preparing specification.



MOHM CHEMICAL SDN. BHD. (Co.No.276851-U)
MCX MARKETING SDN. BHD. (Co.No.363532-T)

H.Q. : No.32,Jalan Temenggong,Off Jalan Tampoi, 81100 Johor Bahru, Johor. Malaysia.
 Tel : (60 7) 333 1222 Fax : (60 7) 332 0545 / 333 7919
 Branch : No.43,Jalan Tambur 33/19, Sek. 33, Shah Alam Technology Park,
 47100 Shah Alam, Selangor. Malaysia.
 Tel: (60 3) 5124 0876 / 5124 0878 Fax: (60 3) 5124 0877
 Email: info@mochem.com Website: www.mochem.com / www.xtraseal.com



MATERIAL SAFETY DATA SHEET

xtraseal® **LOW VOC MC-800 ACRYLIC SEALANT**



10. Stability and Reactivity

Chemical stability:	Stable
Incompatibility (material to be avoid):	None known
Conditions to be avoid:	None known
Dangerous reactions:	None known.
Dangerous products of decomposition:	No dangerous decomposition products known.

11. Toxicological Information

Acute toxicity:	Not determined
Primary irritant effect, On the skin:	Irritant for skin and mucous membranes.
On the eye:	Irritant effect
Additional Toxicological information:	When used and handled according to specification, the product does not have any harmful effects according to our experience and the information provided to us.

12. Ecological Information

Complete information not yet available.

13. Disposal considerations

For cured sealant landfill may be suitable.
 With respect to local regulation, dispose of to suitable incineration plant.

14. Transport Information

Proper shipping name:	Latex based Acrylic Sealant
Hazard technical name:	Not available.
Hazard class:	Not available.
No dangerous goods under the transport regulation.	

15. Regulatory Information

Labeling (EC): This product is not subject to the labeling requirements of EC directives.



MOHM CHEMICAL SDN. BHD. (Co.No.276851-U)
MCX MARKETING SDN. BHD. (Co.No.363532-T)

H.Q. : No.32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor. Malaysia.
Tel : (60 7) 333 1222 Fax : (60 7) 332 0545 / 333 7919
Branch : No.43, Jalan Tambur 33/19, Sek. 33, Shah Alam Technology Park,
47100 Shah Alam, Selangor. Malaysia.
Tel: (60 3) 5124 0876 / 5124 0878 Fax: (60 3) 5124 0877
Email: info@mochem.com Website: www.mochem.com / www.xtraseal.com



MATERIAL SAFETY DATA SHEET

xtraseal® **LOW VOC MC-800 ACRYLIC SEALANT**



16. Other Information

These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use and determine whether they are appropriate.

*** End Of MSDS ***