



MOHM CHEMICAL SDN. BHD. (Co.No.276851-U)
MCX MARKETING SDN. BHD. (Co.No.363532-T)

H.Q. : No.32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor. Malaysia.

Tel : (60 7) 333 1222 Fax : (60 7) 332 0545 / 333 7919

Branch : No.43, Jalan Tambur 33/19, Sek. 33, Shah Alam Technology Park,
47100 Shah Alam, Selangor. Malaysia.

Tel: (60 3) 5124 0876 / 5124 0878 Fax: (60 3) 5124 0877

Email: info@mochem.com Website: www.mochem.com / www.xtraseal.com

MATERIAL SAFETY DATA SHEET

xtraseal[®] 3 TON EPOXY

1. Product & Company Identification

Product Detail

Product name: 3 Ton Epoxy
Physical form: Liquid
Odour: Characteristic Odour
CAS No.: Mixture
Flammability: Combustible.

Company Details:

Manufacturer: Mohm Chemical Sdn Bhd
Address: No. 32 (Lot 1617), Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor, Malaysia.
Tel: + 60-7-3331222
Fax: + 60-7-3320545/ + 60-7-3337919

2. Composition/ Hazardous Components

<u>Chemical Name</u>	<u>CAS No.</u>	<u>Approx WT%</u>
Diphenylolpropane Epoxy Resin	80-05-7	
Polyamines	904610-0	

3. Hazards Identification

Ingestion: Irritation of the mouth, throat and stomach.
Skin contact: May cause sensitization by skin contact.
Inhalation: Harmful by inhalation
Eye contact: May irritates eyes.

4. First-aid Measures

Take off all contaminated clothing immediately.
In case of ingestion: Seek medical advice immediately.
In case of skin contact: Wipe with paper towel and immediately clean with water and soap.
In case of eyes contact: immediately flush with water, seek medical advice if necessary.
In case of inhalation: Removed to fresh air, keep warm and rest.

5. Fire Fighting Measures

Suitable extinguishing media: Use dry chemical powder, foam, carbon dioxide, water fog, sand and earth.
Unsuitable extinguishing media: Water from a jet.
Hazardous decomposition: Carbon dioxide, carbon monoxide.



MOHM CHEMICAL SDN. BHD. (Co.No.276851-U)
MCX MARKETING SDN. BHD. (Co.No.363532-T)



H.Q. : No.32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor. Malaysia.
 Tel : (60 7) 333 1222 Fax : (60 7) 332 0545 / 333 7919
 Branch : No. 43, Jalan Tambur 33/19, Sek. 33, Shah Alam Technology Park,
 47100 Shah Alam, Selangor. Malaysia.
 Tel: (60 3) 5124 0876 / 5124 0878 Fax: (60 3) 5124 0877
 Email: info@mochem.com Website: www.mochem.com / www.xtraseal.com

MATERIAL SAFETY DATA SHEET

x'traseal® 3 TON EPOXY

6. Accidental release measures

Exclude sources of ignition and ventilate the area.
 Avoid breathing vapours.
 Methods for cleaning up: Take up mechanically.

7. Handling and Storage

Handling: Avoid contact with eyes and skin. Ensure good ventilation during processing. Wear safety goggles and gloves.
 Protection against fire/ explosion: General rules of fire prevention should be observed.
 Storage: Keep container tightly closed and dry. Store in cold and well-ventilated area.

8. Exposure control/ Personal protection

Ingredients with limited values to be controlled: Not indicated.
 Local exhaust: Recommended
 General ventilation: Recommended
 Hand protection: Suitable protective gloves.
 Eye protection: Safety/ protective glasses.

9. Physical and Chemical Properties

3 Ton Epoxy Resin
 Form: Viscous Liquid
 Colour: Clear
 Specific gravity: 1.16
 Viscosity: 8,000cps @Spindle No.4, 50rpm, 28°C
 Odour: Characteristic Odour
 Epoxy Molar Mass: 182 –194g
 Boiling point: >200°C
 Freezing Point: Crystals sometimes separate at room temperature
 Flash point: >150°C
 Ignition temperature: >300°C
 Solubility in water: Immiscible
 Incompatibilities: React with acids and bases

3 Ton Epoxy Hardener
 Form: Viscous Liquid
 Colour: Amber
 Specific gravity: 0.97
 Viscosity: 30,000cps @ Spindle No.4, 50rpm, 28°C.
 Odour: Characteristic smell.
 Amine Value: 300 - 360
 Flash point: >265°C.

Note: the above information is not intended for use in preparing specification.



MOHM CHEMICAL SDN. BHD. (Co.No.276851-U)
MCX MARKETING SDN. BHD. (Co.No.363532-T)



H.Q. : No.32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor. Malaysia.
 Tel : (60 7) 333 1222 Fax : (60 7) 332 0545 / 333 7919
 Branch : No. 43, Jalan Tambur 33/19, Sek. 33, Shah Alam Technology Park,
 47100 Shah Alam, Selangor. Malaysia.
 Tel: (60 3) 5124 0876 / 5124 0878 Fax: (60 3) 5124 0877
 Email: info@mochem.com Website: www.mochem.com / www.xtraseal.com

MATERIAL SAFETY DATA SHEET

x'traseal® 3 TON EPOXY

10. Stability and Reactivity

Chemical stability:	Stable
Incompatibility (material to be avoid):	Acids and bases.
Conditions to be avoid:	High temperature
Dangerous reactions:	None known.
Dangerous products of decomposition:	Carbon dioxide, carbon monoxide.

11. Toxicological Information

Acute toxicity:	Not determined
Primary irritant effect, On the skin:	Irritant for skin and mucous membranes
On the eye:	Irritant effect
Sensitization:	Sensitization possible by inhalation
Additional Toxicological information:	When used and handled according to specification, the product does not have any harmful effects according to the information provided to us.

12. Ecological Information

Complete information not yet available.

13. Disposal Considerations

Do not allow large quantities to enter the drains or water courses or dispose of where ground or surface waters may be affected. Residues in emptied containers should be covered and should be disposing of respect to local regulations.

14. Transport Information

Proper shipping name:	Epoxy
Hazard technical name:	Not available.
Hazard class:	Not available.
No dangerous goods under the transport regulation.	



MOHM CHEMICAL SDN. BHD. (Co.No.276851-U)
MCX MARKETING SDN. BHD. (Co.No.363532-T)



H.Q. : No.32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor. Malaysia.
 Tel : (60 7) 333 1222 Fax : (60 7) 332 0545 / 333 7919
 Branch : No. 43, Jalan Tambur 33/19, Sek. 33, Shah Alam Technology Park,
 47100 Shah Alam, Selangor. Malaysia.
 Tel: (60 3) 5124 0876 / 5124 0878 Fax: (60 3) 5124 0877
 Email: info@mochem.com Website: www.mochem.com / www.xtraseal.com

MATERIAL SAFETY DATA SHEET

x'traseal[®] 3 TON EPOXY

15. Regulatory Information

Labeling (EC): This product is classified and labeled for supply in accordance with the classification of hazardous chemical.

Classification:	Harmful Irritant to skin	
Risk Phrases:	R43 R36/38	May causes sensitization by skin contact. Irritant to skin
Safety Phrases:	S2 S28 S26 S27 S37 S46	Keep out of reach of children. After contact with skin, wash immediately with plenty of water. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Take off immediately all contaminated clothing. Wear suitable gloves. If swallowed, seek medical advice immediately and show this container or label.

16. Other Information

These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use and determine whether they are appropriate.

*** End Of MSDS ***