



MOHM CHEMICAL SDN. BHD. (Co.No.276851-U)
MCX MARKETING SDN. BHD. (Co.No.363532-T)



H.Q. : No.32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor. Malaysia.
 Tel : (60 7) 333 1222 Fax: (60 7) 332 0545 / 333 7919
 Branch : No. 43, Jalan Tambur 33/19, Sek. 33, Shah Alam Technology Park,
 47100 Shah Alam, Selangor. Malaysia.
 Tel: (60 3) 5124 0876 / 5124 0878 Fax: (60 3) 5124 0877
 Email: info@mochem.com Website: www.mochem.com / www.xtraseal.com

MATERIAL SAFETY DATA SHEET

x'traseal® PS-200 PVC PIPE ADHESIVE

1. Product & Company Identification

1.1 Product Detail	
Product name:	PS-200 PVC PIPE ADHESIVE
Physical form:	Viscous Liquid
Odour:	Aromatic Odour
CAS No.:	Mixture
Flammability:	Highly Flammable
1.2 Company Details:	
Manufacturer:	Mohm Chemical Sdn Bhd
Address:	No. 32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor, Malaysia.
Tel:	+ 60-7-3331222
Fax:	+ 60-7-3320545/ + 60-7-3337919

2. Composition/ Hazardous Components

<u>Chemical Name</u>	<u>%</u>	<u>Hazard</u>
PVC Resin	< 17	None currently known
Ketone Solvent	> 83	Flammable, Irritant, Harmful by inhalation

3. Hazards Identification

Ingestion:	Harmful.
Skin contact:	Uncured product contact will irritate lips, gums and tongue. Uncured product contact may irritate the skin.
Inhalation:	High vapour concentrations may cause irritation, headache and dizziness.
Eye contact:	Uncured product contact irritates eyes.

4. First-aid Measures

Take off all contaminated clothing immediately.	
In case of inhalation	Remove to fresh air, keep warm and at rest.
In case of skin contact:	Removed contaminated clothing. Rinse with water and use a proprietary skin cleaner immediately.
In case of eyes contact:	Contact lenses should be removed. Rinse with plenty of water Immediately, seek medical advice if necessary.
Advice to doctor:	Treat symptomatically.



MOHM CHEMICAL SDN. BHD. (Co.No.276851-U)
MCX MARKETING SDN. BHD. (Co.No.363532-T)



H.Q. : No.32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor. Malaysia.
 Tel : (60 7) 333 1222 Fax : (60 7) 332 0545 / 333 7919
 Branch : No. 43, Jalan Tambur 33/19, Sek. 33, Shah Alam Technology Park,
 47100 Shah Alam, Selangor. Malaysia.
 Tel: (60 3) 5124 0876 / 5124 0878 Fax: (60 3) 5124 0877
 Email: info@mochem.com Website: www.mochem.com / www.xtraseal.com

MATERIAL SAFETY DATA SHEET

xtraseal® PS-200 PVC PIPE ADHESIVE

5. Fire Fighting Measures	
Flammability:	Highly Flammable.
Suitable extinguishing media:	Chemical Powder, Foam, CO ² , Water Fog, Sand or Earth
Unsuitable extinguishing media:	Do not use water in a jet

6. Accidental release measures	
Methods:	Exclude sources of ignition and ventilation the area Exclude non-essential personnel. Avoid breathing vapour Collect spillages mechanically and store in suitable covered container

7. Handling and Storage	
Handling:	Ensure good ventilation during processing. Wear safety shoes.
Protection against fire/ explosion:	General rules of fire prevention should be observed.
Storage:	Keep container tightly closed and dry. Store in a well-ventilated area.

8. Exposure control/ Personal protection	
Industrial Hygiene:	Remove immediately all contaminated clothing. Do not inhale vapour.
Hand protection:	Suitable protective gloves.
Eye protection:	Safety / Protective Goggles

9. Physical and Chemical Properties	
Form:	Viscous liquid
Specific gravity:	0.88 ± 0.02
Colour:	Colourless
Viscosity:	160-200 cps
Odour:	Aromatic odour
Solid Content	16 ± 1%
Melting Temperature	Not Applicable
Boiling point:	79 – 82 °C
Flash point:	- 4 °C
Freezing Point	- 86.4 °C
Ignition Temperature:	Non known
Vapour Pressure (25°C)	Non known
Soluble in Water (25°C)	Insoluble

Note: the above information is not intended for use in preparing specification.



MOHM CHEMICAL SDN. BHD. (Co.No.276851-U)
MCX MARKETING SDN. BHD. (Co.No.363532-T)



H. Q. : No.32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor. Malaysia.
 Tel : (60 7) 333 1222 Fax: (60 7) 332 0545 / 333 7919
 Branch : No. 43, Jalan Tambur 33/19, Sek. 33, Shah Alam Technology Park,
 47100 Shah Alam, Selangor. Malaysia.
 Tel: (60 3) 5124 0876 / 5124 0878 Fax: (60 3) 5124 0877
 Email: info@mochem.com Website: www.mochem.com / www.xtraseal.com

MATERIAL SAFETY DATA SHEET

x'traseal® PS-200 PVC PIPE ADHESIVE

10. Stability and Reactivity	
Hazardous Decomposition Products	None
Hazardous Reaction	No dangerous reaction known

11. Toxicological Information	
On the skin:	May cause sensitization
On the eye:	Possibility irritating

12. Ecological Information	
Large quantities of products should not be allowed to enter drains or watercourses or be deposited where it can affect ground or surface water.	

13. Disposal considerations	
Do not allow large quantities to enter the drains or watercourses or dispose of where ground surface may be affected. Residue in emptied containers should be covered and should be disposed of in accordance with regulations made under the control of Pollution & Environment Protection Acts.	

14. Transport Information	
ICAO/IATA-DGR: CLASS 3, FLAMMABLE LIQUID, UN CODE 1133, PACKING: GROUP II	

15. Regulatory Information	
The product is classified and labeled for supply in accordance with the Classification Of Hazardous Chemical. Regulations as follow :-	
Classification	Highly Flammable Harmful Flammable Irritant to skin
R-phrases 43	May causes sensitization by skin contact
36/38	Irritant to skin
S-phrases Z	Keep out of reach of children
28	After contact with skin, wash immediately with plenty of water
26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advise
27	Take off immediately all contaminated clothing
37	Wear suitable gloves
46	If swallowed, seek medical advice immediately and shoe this container or label
Labeling (EC):	



MOHM CHEMICAL SDN. BHD. (Co.No.276851-U)
MCX MARKETING SDN. BHD. (Co.No.363532-T)

H.Q. : No.32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor. Malaysia.

Tel : (60 7) 333 1222 Fax : (60 7) 332 0545 / 333 7919

Branch : No. 43, Jalan Tambur 33/19, Sek. 33, Shah Alam Technology Park,
47100 Shah Alam, Selangor. Malaysia.

Tel: (60 3) 5124 0876 / 5124 0878 Fax: (60 3) 5124 0877

Email: info@mochem.com Website: www.mochem.com / www.xtraseal.com

MATERIAL SAFETY DATA SHEET

x'traseal[®] PS-200 PVC PIPE ADHESIVE

16. Other Information

These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use and determine whether they are appropriate.

*** End of MSDS ***

