



MOHM CHEMICAL SDN. BHD. (Co.No.276851-U)
MCX MARKETING SDN. BHD. (Co.No.363532-T)

H.Q. : No.32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor, Malaysia.
Tel : (60 7) 333 1222 Fax: (60 7) 332 0545 / 333 7919
Branch : No.43, Jalan Tambur 33/19, Sek. 33, Shah Alam Technology Park,
47100 Shah Alam, Selangor, Malaysia.
Tel: (60 3) 5124 0876 / 5124 0878 Fax: (60 3) 5124 0877
Email: info@mochem.com Website: www.mochem.com / www.xtraseal.com

TECHNICAL DATA SHEET

xtraseal® BT-390 WINDSCREEN SEALANT

DESCRIPTION:

xtraseal® BT-390 WINDSCREEN SEALANT (BUTYL TAPE) IS A BLACK, NON-HARDENING SYNTHETIC RUBBER BASED. IT IS A STICKY RIBBON TYPE AUTO GLASS REPLACEMENT SEALER USED FOR THE INSTALLATION OF ALL GASKETS LESS WINDSHIELDS AND BACKLITES. BT-390 OFFERS A FAST AND CLEAN METHOD FOR INSTALLING THE GLASS. INSTANTLY WITH SUPERIOR ADHESION. THE SEALER HAS EXCELLENT COMPRESSIBILITY IN BOTH LOW / HIGH TEMPERATURES. IT IS DESIGNED T MAINTAIN POSITION, PERMANENTLY SEALING AND WATERPROOFING BETWEEN THE GLASS AND PINCH WELD.

SPECIFICATION:

BASE	BUTYL RUBBER
APPEARANCE	BLACK
HARDNESS IRHD	25 ± 1
SPECIFIC GRAVITY	1.4 ± 0.10

PROPERTIES:

HEAT RESISTANCE (16h/150°C)	100°C
WATER RESISTANCE	EXCELLENCE
SERVICE TEMPERATURE	- 20°C to 70°C
ORDOR	NON OR VERY LITTLE
ADHESION	GOOD ON METAL, GLASS, WOOD AND CONCRETE
STORAGE	PRODUCT IS VERY INERT AND CAN LAST ALMOST INDEFINITELY WITHOUT DETERIORATING

APPLICATION:

- ◆ REMOVE THE WINDSHIELDS AND OLD SEALANT MATERIAL FROM SURFACES THOROUGHLY.
- ◆ SURFACE MUST BE CLEAN, DRY AND FREE FROM GREASE, OIL AND DIRT.
- ◆ HAND PRESSED THE TAPE INTO PLACE GROUND THE PINCH WELD. REPLACE NEW SETTING BLOCKS IF ORIGINAL BLOCKS ARE DAMAGED.
- ◆ PLACE THE WINDSCREEN OVER THE TAPE AND APPLY PRESSURE EVENLY TO ENSURE WATER TIGHT ACHIEVED.

TIPS:

- ◆ THIS TAPE CAN BE USED ALONE OR IN COMBINATION WITH OTHER SEALANTS, EG. POLYURETHANE OR SILICONE SEALANT DEPENDING UPON THE TYPE OF INSTALLATION.
- ◆ IN EXTREMELY COLD WEATHER CONDITIONS, IT IS RECOMMENDED TO WARM THE BUTYL TAPE FOR THE BETTER WORKABILITY.



MOHM CHEMICAL SDN. BHD. (Co.No.276851-U)
MCX MARKETING SDN. BHD. (Co.No.363532-T)

H.Q. : No.32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor, Malaysia.

Tel : (60 7) 333 1222 Fax : (60 7) 332 0545 / 333 7919

Branch : No.43, Jalan Tambur 33/19, Sek. 33, Shah Alam Technology Park,
47100 Shah Alam, Selangor, Malaysia.

Tel: (60 3) 5124 0876 / 5124 0878 Fax: (60 3) 5124 0877

Email: info@mochem.com Website: www.mochem.com / www.xtraseal.com

TECHNICAL DATA SHEET

x'traseal® BT-390 WINDSCREEN SEALANT

CAUTION:

AVOID EYE AND PROLONGED SKIN CONTACT IF CONTACTED EYE, FLUSH WITH PLENTY OF WATER; SEEK PHYSICIAN IF IRRITATION PERSISTS. STORE UNDER SHADED AREA. KEEP OUT OF REACH OF CHILDREN.

