



MOHM CHEMICAL SDN. BHD. (Co.No.276851-U)
MCX MARKETING SDN. BHD. (Co.No.363532-T)

H.Q. : No.32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor. Malaysia.
Tel : (60 7) 333 1222 Fax : (60 7) 332 0545 / 333 7919
Branch : No.43, Jalan Tambur 33/19, Sek. 33, Shah Alam Technology Park,
47100 Shah Alam, Selangor. Malaysia.
Tel: (60 3) 5124 0876 / 5124 0878 Fax: (60 3) 5124 0877
Email: info@mochem.com Website: www.mochem.com / www.xtraseal.com

TECHNICAL DATA SHEET

x'traseal® EPOXY PUTTY STICK

Description:

x'traseal® Epoxy Stick is a hand kneadable, two part, co-extruded, fast curing epoxy putty, specially prepared to work on diverse materials. It is very easy to use and useful for emergency repairs in industries, workshops, marine, automotive, construction and also for household use. Good for wet surfaces.

Features:

- ◆ Instant Emergency
- ◆ Permanent Repair
- ◆ Multipurpose
- ◆ Underwater Repair

Uses:

Permanent repair: leaks, holes, cracks, mounting signs to walls.

Suitable Substrates: metal, fiberglass, concrete, ceramics and many plastic materials. Works in damp, wet and slowly leaking area.

Applications:

- ◆ Cut the required quantity of putty stick
- ◆ Mix homogenously until mixture gets uniform color
- ◆ Apply immediately on clean surface
- ◆ For best adhesion roughen the surface
- ◆ Wear protective eye glasses & hand gloves whenever necessary

Physical Properties:

Work Life	5 to 7 Minutes
Curing Time	12 to 16 Minutes
Shelf Life	12 Months
Hardness	Shore D - 82
Safe Working Temperature	Up to 120°C
Nonvolatile Content	100%
Compression Strength	600 kg/cm ²
Tensile Strength	45 kg/cm ²
Excellent resistance to hydro carbons, moisture, saline weather and saline water, oil, minerals, solvents, mild acids and alkalies, etc.	



MOHM CHEMICAL SDN. BHD. (Co.No.276851-U)
MCX MARKETING SDN. BHD. (Co.No.363532-T)

H.Q. : No.32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor. Malaysia.
Tel : (60 7) 333 1222 Fax : (60 7) 332 0545 / 333 7919
Branch : No.43, Jalan Tambur 33/19, Sek. 33, Shah Alam Technology Park,
47100 Shah Alam, Selangor. Malaysia.
Tel: (60 3) 5124 0876 / 5124 0878 Fax: (60 3) 5124 0877
Email: info@mochem.com Website: www.mochem.com / www.xtraseal.com

TECHNICAL DATA SHEET

xtraseal[®] EPOXY PUTTY STICK

Caution:

- ◆ Normally, while mixing by hand it does not cause any skin irritation, but in some cases with sensitive skins, it may cause irritation or sensitization. In such cases, wash the hands with plenty of water and soap and use hand gloves for application.
- ◆ In case of contact with eye, wash with plenty of water and consult physician immediately
- ◆ If swallowed, it may be harmful
- ◆ Keep away from children
- ◆ While grinding, sanding or drilling, wear protective eye glasses and dust masks
- ◆ The cured mass of epoxy is generally nontoxic

Warranty:

All matter mentioned in this sheet is reliable and correct to the best our knowledge, but we not accept any liabilities resulting from the use of this product. The users should rely on their own information and tests to determine the suitability of the product for required application. Manufacturer shall not be liable for any injury, loss or damage, resulting from use or misuse of the product, directly or indirectly.