



MOHM CHEMICAL SDN. BHD. (Co. No. 275851-U)

MCX MARKETING SDN. BHD. (Co. No. 363532-T)

H.Q. : No. 32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor, Malaysia.
Tel: (60) 7 333 1222 Fax: (60) 7 332 0545/ 333 7919

Branch: No. 43, Jalan Tambur 33/19, Sek. 33, Shah Alam Technology Park,
40400 Shah Alam, Selangor, Malaysia.
Tel: (60) 3 5124 0876/ 5124 0878 Fax: (60) 3 5124 0877

Email: Info@mochem.com Website: www.mochem.com / www.xtraseal.com

TECHNICAL DATA SHEET

xtraseal® SNOW FILLER

DESCRIPTION:

xtraseal SNOW FILLER IS A READY-MIXED LIGHTWEIGHT FILLER FOR QUICK AND SIMPLE REPAIRS. IT IS SPECIALLY FORMULATED FOR REPAIRS WALLS AND CEILINGS. IDEAL FOR FILLING LARGE OR SMALL HOLES, NAILHEADS, NAIL HOLE, CRACKS IN CONCRETE, MASONRY, PLASTER AND WOOD. EASY TO APPLY, DRIES FAST AND WILL NOT CRACK, SHRINK OR SAG. SUITABLE FOR INTERNAL USE ONLY.

FEATURES:

- ◆ ONLY ONE APPLICATION NEEDED.
- ◆ ONE PART NO MIXING.
- ◆ ENVIRONMENTAL FRIENDLY, EASILY CLEAN UP WITH WATER.
- ◆ MINIMAL SHRINKAGE AND CRACKING.
- ◆ FAST DRYING AND CAN BE SANDED AND PAINTED AFTER SET.
- ◆ WHITE COLOR.

LIMITATIONS:

SNOW FILLER IS LESS-FLEXIBLE FILLING COMPOUND AND ONLY RECOMMENDED FOR INTERNAL USE ONLY.

NOT FOR: USE IN AREAS OF WATER IMMERSION.

NOT FOR: NAILING OR STRONG SUPPORTING.

NOT FOR: USE ON PLASTIC OR METAL SURFACES.

NOT FOR: MOVEMENT JOINT

COLOUR:

WHITE

APPLICATION:

- ◆ SURFACE MUST BE CLEAN, DUST AND GREASE FREE.
- ◆ APPLY FILLER WITH A PUTTY KNIFE INTO THE CRACK OR GAP WHICH REQUIRES FILLING. IF THE FILLER FEELS TOO DRY, MIX WITH A FEW DROPS OF WATER.
- ◆ FILL ALL SIZES OF HOLES AND CRACKS IN ONE APPLICATION.
- ◆ SMOOTH FINISH IN ONE STROKE USING A PUTTY KNIFE.
- ◆ SANDABLE AND PAINTABLE AFTER CURING.
- ◆ CLEAN TOOLS WITH WATER IMMEDIATELY AFTER USE.

CURING TIME:

SNOW FILLER WILL SET WITHIN 30 MINUTES. LONGER DRYING TIMES MAY BE NECESSARY FOR LARGE HOLES OR IN COLD AND HIGH HUMIDITY AREA.



MOHM CHEMICAL SDN. BHD. (Co. No. 275851-U)

MCX MARKETING SDN. BHD. (Co. No. 363532-T)

H.Q. : No. 32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor, Malaysia.

Tel: (60) 7 333 1222 Fax: (60) 7 332 0545/ 333 7919

Branch: No. 43, Jalan Tambur 33/19, Sek. 33, Shah Alam Technology Park,
40400 Shah Alam, Selangor, Malaysia.

Tel: (60) 3 5124 0876/ 5124 0878 Fax: (60) 3 5124 0877

Email: Info@mochem.com Website: www.mochem.com/ www.xtraseal.com

TECHNICAL DATA SHEET

xtraseal® SNOW FILLER

SPECIFICATION:

BASE	ACRYLIC LATEX
APPEARANCE	NON-SAGGING PASTE
COLOUR	WHITE
SPECIFIC GRAVITY	0.45 ± 0.1
SOLID CONTENTS	70% ± 10%
TACK FREE TIME	30 MINUTES
APPLICATION TEMP.	5°C TO 50°C
SERVICE TEMP.	-10°C TO 80°C
SHELF LIFE	12 MONTHS

CAUTION:

USE APPROPRIATE PERSONAL PROTECTION TO AVOID CONTACT WITH SKIN AND EYES.
IN CASE OF EYE CONTACT OR IRRITATION, FLUSH EYE IMMEDIATELY WITH RUNNING WATER
FOR 15 MINUTES AND GET MEDICAL ATTENTION.
IN CASE OF SKIN CONTACT, WASH AFFECTED AREAS WITH HAND CLEANER FOLLOWED BY
SOAP AND WATER.
FOR FURTHER HEALTH AND SAFETY INFORMATION CONSULT THE CURRENT MATERIAL
SAFETY DATA SHEET.