



**MOHM CHEMICAL SDN. BHD.** (Co. No. 275851-U)

**MCX MARKETING SDN. BHD.** (Co. No. 363532-T)

H.Q. : No. 32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor, Malaysia.

Tel: (60) 7 333 1222 Fax: (60) 7 332 0545/ 333 7919

Branch: No. 43, Jalan Tambur 33/19, Sek. 33, Shah Alam Technology Park,  
40400 Shah Alam, Selangor, Malaysia.

Tel: (60) 3 5124 0876/ 5124 0878 Fax: (60) 3 5124 0877

Email: [Info@mochem.com](mailto:Info@mochem.com) Website: [www.mochem.com](http://www.mochem.com) / [www.xtraseal.com](http://www.xtraseal.com)

## TECHNICAL DATA SHEET

### xtraseal® WOOD FILLER

#### DESCRIPTION:

**xtraseal®** WOOD FILLER IS A CELLULOSE FIBRE READY MIXED HIGH PERFORMANCE WATER BASED FILLER THAT GIVE A TOUGH AND SMOOTH SANDABLE SURFACE AFTER DRIED, IT CAN BE STAINED, VARNISHED, PAINTED AND ACT LIKE REAL WOOD.

#### FEATURES:

- ◆ LOW ODOR.
- ◆ HARD AND SMOOTH SURFACE.
- ◆ ONE PART NO MIXING.
- ◆ ENVIRONMENTAL FRIENDLY, EASILY CLEAN UP WITH WATER BEFORE CURED.
- ◆ GOOD ADHESION TO WOOD, CONCRETE, METAL AND MARBLE.

#### USES:

- ◆ DIY APPLICATION: FURNITURE, PANELLING, DOORS, PLYWOOD PATCHING.

#### LIMITATIONS:

NOT FOR: USE IN AREAS OF CONSTANT WATER IMMERSION.  
NOT FOR: JOINT MOVEMENT.

#### COLOUR:

NATURAL, TEAK.

#### APPLICATION:

- ◆ SURFACE TO BE FILLED MUST BE CLEAN AND DRY.
- ◆ MASK SMOOTH SURFACE TO SIMPLIFY CLEAN UP.
- ◆ APPLY WOOD FILLER FIRMLY INTO PLACE WITH A PUTTY KNIFE.
- ◆ FILL UP SLIGHTLY HIGHER SURFACE TO ALLOW FOR SANDING.
- ◆ SAND AFTER 30MINUTES ON SHALLOW REPAIRS, DEEP REPAIRS AFTER 2-8HOURS.
- ◆ USE MEDIUM SAND PAPER, DO NOT CONTINUOUS HIGH SPEED SANDING.

#### CURING TIME:

WOOD FILLER WILL DRIED IN APPROXIMATELY 30 MINUTES AND WILL CURE TO A DEPTH OF 5mm IN 1-2DAYS.



**MOHM CHEMICAL SDN. BHD.** (Co. No. 275851-U)

**MCX MARKETING SDN. BHD.** (Co. No. 363532-T)

H.Q. : No. 32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor, Malaysia.

Tel: (60) 7 333 1222 Fax: (60) 7 332 0545/ 333 7919

Branch: No. 43, Jalan Tambur 33/19, Sek. 33, Shah Alam Technology Park,  
40400 Shah Alam, Selangor, Malaysia.

Tel: (60) 3 5124 0876/ 5124 0878 Fax: (60) 3 5124 0877

Email: [Info@mochem.com](mailto:Info@mochem.com) Website: [www.mochem.com](http://www.mochem.com) / [www.xtraseal.com](http://www.xtraseal.com)

## TECHNICAL DATA SHEET

### x'traseal® WOOD FILLER

#### **SPECIFICATION:**

BASE	VINYL ACETATE LATEX
APPEARANCE	NON-SAGGING PASTE
COLOUR	NATURAL, TINT.
SPECIFIC GRAVITY	1.65 ± 0.05
SOLID CONTENTS	80% ± 2%
TACK FREE TIME	10 MINUTES
APPLICATION TEMP.	5°C TO 50°C
SERVICE TEMP.	-10°C TO 80°C
SHELF LIFE	12 MONTHS

#### **CAUTION:**

USE APPROPRIATE PERSONAL PROTECTION TO AVOID CONTACT WITH SKIN AND EYES.

IN CASE OF EYE CONTACT OR IRRITATION, FLUSH EYE IMMEDIATELY WITH RUNNING WATER FOR 15 MINUTES AND GET MEDICAL ATTENTION.

IN CASE OF SKIN CONTACT, WASH AFFECTED AREAS WITH HAND CLEANER FOLLOWED BY SOAP AND WATER.

FOR FURTHER HEALTH AND SAFETY INFORMATION CONSULT THE CURRENT MATERIAL SAFETY DATA SHEET.