



MOHM CHEMICAL SDN. BHD. (Co. No. 276851-U)

MCX MARKETING SDN. BHD. (Co. No. 363532-T)

H.Q. : No. 32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor, Malaysia.

Tel: (60) 7 333 1222 Fax: (60) 7 332 0545/ 333 7919

Branch: No. 43, Jalan Tambur 33/19, Sek. 33, Shah Alam Technology Park,
40400 Shah Alam, Selangor, Malaysia.

Tel: (60) 3 5124 0876/ 5124 0878 Fax: (60) 3 5124 0877

Email: info@mochem.com Website: www.mochem.com/ www.xtraseal.com

TECHNICAL DATA SHEET

x'traseal® x'mastic NON SKINNING SEALANT

DESCRIPTION :

x'traseal® x-mastic IS A ONE COMPONENT, NON-DRYING POLYBUTENE RUBBER BASED MASTIC THAT DOES NOT HARDEN BUT RATHER REMAINS PERMANENTLY SOFT AND PASTE-LIKE. EXCELLENT RESISTANCE TO WATER VAPOUR TRANSMISSION.

FEATURES :

- ◆ PERMANENTLY NON-SKINNING.
- ◆ LOW SHRINKAGE.
- ◆ MOISTURE RESISTANCE.
- ◆ EXCELLENT ADHESION.

USES :

IT'S SUITABLE FOR ALL KINDS OF PLASTICS, METALS, GLASS, MASONRY AND TIMBER. IT ALSO CAN BE USED IN THE INSTALLATION OF COOLROOMS AND PREFABRICATED CONSTRUCTION.

LIMITATIONS :

IT SHOULD NOT BE APPLIED IN EXPOSED JOINTS WHERE DIRT PICK-UP AND HAND CONTACT.

NOT FOR: USED IN AREAS SUBJECT TO CONSIDERATE DYNAMIC STRESS.

NOT FOR: MOBILE HOMES, TRUCK BODIES.

COLOUR: WHITE, ALMOND. OTHER COLOURS ARE AVAILABLE UPON REQUEST.

APPLICATION:

- ◆ SURFACE MUST BE CLEAN AND DRY.
- ◆ CUT NOZZLE TO DESIRED SIZE.
- ◆ INSERT CARTRIDGE INTO CAULKING GUN.
- ◆ PUSH SEALANT AHEAD FOR UNIFORM BEAD.
- ◆ CLEAN OFF EXCESS SEALANT WITH KEROSENE OR MINERAL SPIRITS.

SPECIFICATION :

FORM	NON-SAGGING PASTE.
COLOUR	WHITE
SPECIFIC GRAVITY	1.60±0.2
SLUMP	2.5 MM MAXIMUM
SHRINKAGE	5 % MAXIMUM
SERVICE TEMP.	- 40° C TO 80° C



MOHM CHEMICAL SDN. BHD. (Co. No. 276851-U)

MCX MARKETING SDN. BHD. (Co. No. 363532-T)

H.Q. : No. 32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor, Malaysia.
Tel: (60) 7 333 1222 Fax: (60) 7 332 0545/ 333 7919

Branch: No. 43, Jalan Tambur 33/19, Sek. 33, Shah Alam Technology Park,
40400 Shah Alam, Selangor, Malaysia.

Tel: (60) 3 5124 0876/ 5124 0878 Fax: (60) 3 5124 0877

Email: info@mochem.com Website: www.mochem.com / www.xtraseal.com

TECHNICAL DATA SHEET

x'traseal® x'mastic NON SKINNING SEALANT

CAUTION:

USE APPROPRIATE PERSONAL PROTECTION TO AVOID CONTACT WITH SKIN AND EYES.

IN CASE OF EYE CONTACT OR IRRITATION, FLUSH EYE IMMEDIATELY WITH RUNNING WATER FOR 15 MINUTES AND GET MEDICAL ATTENTION.

IN CASE OF SKIN CONTACT, WASH AFFECTED AREAS WITH HAND CLEANER FOLLOWED BY SOAP AND WATER.

FOR FURTHER HEALTH AND SAFETY INFORMATION CONSULT THE CURRENT MATERIAL SAFETY DATA SHEET.

